



Sign Schedule			
	ID: 001	Qty: 2	Ref: 645 End panel
	ID: 002	Qty: 4	Ref: 543 Traffic signals ahead
	ID: 003	Qty: 1	Ref: 518 Single file traffic
	ID: 004	Qty: 1	Ref: 517 Road narrows on one side only ahead - right
	ID: 005	Qty: 4	Ref: 7011 When Red Light Shows Wait Here
	ID: 006	Qty: 2	Ref: 13.9 Schedule 13-9: Temporary Information
	ID: 007	Qty: 1	Ref: 2702 Start of temporary diversion route
	ID: 008	Qty: 1	Ref: 613 No left turn
	ID: 009	Qty: 1	Ref: 610 Keep left
	ID: 010	Qty: 2	Ref: 7016 Crossing not in use [sign for pedestrians]
	ID: 011	Qty: 2	Ref: 573 Direction to hazard left
	ID: 012	Qty: 7	Ref: 7001 Road works ahead
	ID: 013	Qty: 5	Ref: 7202.1 Temporary lane availability
	ID: 014	Qty: 1	Ref: 7105 Lane closure barrier
	ID: 015	Qty: 2	Ref: 610 Keep right
	ID: 016	Qty: 3	Ref: 13.9 Schedule 13-9: Temporary Information
	ID: 017	Qty: 11	Ref: 7018 Pedestrian diversion Right
	ID: 018	Qty: 9	Ref: 7018 Pedestrian diversion Left

NOTE

Diversion to be driven prior to the road closure being installed.

Plans for any road closure should be discussed by the designer with the police and any relevant Highways Authorities, if traffic is being diverted on to their network.

FOR DIVERSION DETAILS REFER TO SHEET 2

- NOTES:
- All signs, markings and safety zones will be in accordance with Traffic Signs Manual.
 - Sign locations are indicative only and exact locations will be determined on site.
 - Works Access and Egress locations to be agreed on site and any changes to the design should be reported.

Key:			
	Safety Zone		Works Area
	Road Closed		Sign
	Diversions		Cone Line
	Pedestrian Route		Marshal
	Pedestrian Barrier		TM Operative
	Portable traffic signal		Traffic light phase
	Pedestrian ramp (Fixed to ground)		No Parking Cones
	Temporary pedestrian crossing		

DETAIL B

Single/Dual carriageway 40mph or less - 450mm cones, spacing 1.5m.
Single/Dual carriageway 50mph or more - 750mm cones, spacing 1.5m.
Dual carriageway national speed limit - 750mm cones, spacing 1.5m, relaxation 3m.

- Notes:
- During darkness, warning lights to BS EN 12352:2006 should be provided in accordance with Table A1.3 (Appendix 1).
 - 45° tapers have 1.5m spacing, no relaxations.
 - On motorways and NSL AP Duals with hard shoulders, 1m cones will be required for both standard and relaxation works for lead tapers and the facing wall of lane changes.

DETAIL C1

Single/Dual carriageway 40mph or less - 450mm traffic cones.
Single/Dual carriageway 50mph or more - 750mm traffic cones.

- Notes:
- During darkness, warning lights to BS EN 12352:2006 should be provided in accordance with Table A1.3 (Appendix 1).
 - For relaxation to Detail C1 see Table A1.3 (Appendix 1).

Scan QR for location
EASTINGS & NORTHINGS:
424108 , 323354



Permanent Speed Limit

SAFETY ZONE DIMENSIONS
Sideways Safety Zone : 0.5m
Longways Safety Zone: 0.5m
ALL DIMENSIONS ARE MINIMA



Diversion Length
0 miles

Revision	By	Checked	Approved	Date	Description

Amey

Title: BOROUGH ROAD CYCLE TRACK
PHASE 1A
LANE CLOSURE A5121 DERBY STREET

SHEET 1

Designed	DP	02.10.25	Eng Chk.	x	x
Drawn	DP	02.10.25	Coordination	x	x
Dwg Chk.	DS	02.10.25	Approved	x	x
Scale at A3	1:500	Project	x	Status	x
Drawing No	AUX-TTM-AMEY-493-BOROUGH_RD-CYCLE-SCHEME-PH1A	Rev	C		