



NOTE

Diversion to be driven prior to the road closure being installed.

Plans for any road closure should be discussed by the designer with the police and any relevant Highways Authorities, if traffic is being diverted on to their network.

Sign Schedule	
	ID: 001 Qty: 5 Ref: 543 Traffic signals ahead
	ID: 002 Qty: 5 Ref: 7011 When Red Light Shows Wait Here
	ID: 003 Qty: 1 Ref: 521 Two-way traffic
	ID: 004 Qty: 1 Ref: 7016 Crossing not in use (sign for pedestrians)
	ID: 005 Qty: 2 Ref: 7018 Pedestrian diversion Right
	ID: 006 Qty: 1 Ref: 7018 Pedestrian diversion Left
	ID: 007 Qty: 2 Ref: 652 One way traffic
	ID: 008 Qty: 1 Ref: 573 Direction to hazard right
	ID: 009 Qty: 1 Ref: 573 Direction to hazard left
	ID: 010 Qty: 2 Ref: 645 End panel
	ID: 011 Qty: 7 Ref: 7001 Road works ahead
	ID: 012 Qty: 1 Ref: 7010-FP-13-9 Nature of temporary hazard ahead - Road Closed
	ID: 013 Qty: 2 Ref: 616 No entry
	ID: 014 Qty: 1 Ref: 606 Turn left
	ID: 015 Qty: 1 Ref: 607 One Way Traffic

NOTES:

- All signs, markings and safety zones will be in accordance with Traffic Signs Manual.
- Sign locations are indicative only and exact locations will be determined on site.
- Works Access and Egress locations to be agreed on site and any changes to the design should be reported.

Key:

	Safety Zone		Works Area
	Road Closed		Sign
	Diversion		Cone Line
	Pedestrian Route		Marshal
	Pedestrian Barrier		TM Operative
	Portable traffic signal		Traffic light phase
	Pedestrian ramp (Fixed to ground)		No Parking Cones
	Temporary pedestrian crossing		

DETAIL B

Single/Dual carriageway 40mph or less - 450mm cones, spacing 1.5m.
Single/Dual carriageway 50mph or more - 750mm cones, spacing 1.5m.
Dual carriageway national speed limit - 750mm cones, spacing 1.5m, relaxation 3m.

Notes:

- During darkness, warning lights to BS EN 12352:2006 should be provided in accordance with Table A1.3 (Appendix 1).
- 45° tapers have 1.5m spacing, no relaxations.
- On motorways and NLS AP Duals with hard shoulders, 1m cones will be required for both standard and relaxation works for lead tapers and the facing wall of lane changes.

DETAIL C1

Single/Dual carriageway 40mph or less - 450mm traffic cones.
Single/Dual carriageway 50mph or more - 750mm traffic cones.

Notes:

- During darkness, warning lights to BS EN 12352:2006 should be provided in accordance with Table A1.3 (Appendix 1).
- For relaxation to Detail C1 see Table A1.3 (Appendix 1).

Scan QR for location EASTINGS & NORTHINGS:

424108 , 323354

Permanent Speed Limit

SAFETY ZONE DIMENSIONS
Sideways Safety Zone : 0.5m
Longways Safety Zone: 0.5m
ALL DIMENSIONS ARE MINIMA

Diversion Length

0 miles

Revision	By	Checked	Approved	Date	Description

Title

BOROUGH ROAD CYCLE TRACK
PHASE 2A - 2B
ONE WAY CLOSURE WELLINGTON STREET
WITH DIVERSION
SHEET 2

Designed	DP	03.10.25	Eng. Chk.	x	x
Drawn	DP	03.10.25	Coordination	x	x
Dwg. Chk.	DS	03.10.25	Approved	x	x
Scale at A3	1:500	Project	x	Status	X
Drawing No	AUX-TTM-AMEY-495-BOROUGH_RD-CYCLE-SCHEME-PH2A_B	Rev	B		

A3