



Sign Schedule	
	ID: 001 Qty: 1 Ref: 2702 End of temporary diversion route
	ID: 002 Qty: 3 Ref: 2703 Direction of temporary diversion route from junction ahead
	ID: 003 Qty: 2 Ref: 2703 Direction of temporary diversion route from junction ahead
	ID: 004 Qty: 6 Ref: 2704 Direction of temporary diversion route
	ID: 005 Qty: 4 Ref: 2704 Direction of temporary diversion route
	ID: 006 Qty: 6 Ref: 2703 Direction of temporary diversion route from junction ahead

NOTES:

1. All signs, markings and safety zones will be in accordance with Traffic Signs Manual.

2. Sign locations are indicative only and exact locations will be determined on site.

3. Works Access and Egress locations to be agreed on site and any changes to the design should be reported.

Key:

Safety Zone

Road Closed

Diversions

Pedestrian Route

Pedestrian Barrier

Portable traffic signal

Pedestrian ramp (Fixed to ground)

Temporary pedestrian crossing

Works Area

Sign

Cone Line

Marshal

TM Operative

Traffic light phase

No Parking Cones

DETAIL B

Single/Dual carriageway 40mph or less - 450mm cones, spacing 1.5m.  
Single/Dual carriageway 50mph or more - 750mm cones, spacing 1.5m.  
Dual carriageway national speed limit - 750mm cones, spacing 1.5m, relaxation 3m.

Notes:

1) During darkness, warning lights to BS EN 12352:2006 should be provided in accordance with Table A1.3 (Appendix 1).

2) 45° tapers have 1.5m spacing, no relaxations.

3) On motorways and NSL AP Duals with hard shoulders, 1m cones will be required for both standard and relaxation works for lead tapers and the facing wall of lane changes.

DETAIL C1

Single/Dual carriageway 40mph or less - 450mm traffic cones.  
Single/Dual carriageway 50mph or more - 750mm traffic cones.

Notes:

1) During darkness, warning lights to BS EN 12352:2006 should be provided in accordance with Table A1.3 (Appendix 1).

2) For relaxation to Detail C1 see Table A1.3 (Appendix 1).

Scan QR for location EASTINGS & NORTHINGS:

424108 , 323354

Permanent Speed Limit

SAFETY ZONE DIMENSIONS  
Sideways Safety Zone : 0.5m  
Longways Safety Zone: 0.5m  
ALL DIMENSIONS ARE MINIMA

Diversion Length  
3.7 miles

Revision	By	Checked	Approved	Date	Description

Amey

Title BOROUGH ROAD CYCLE TRACK PHASE 2A - 2B ONE WAY CLOSURE WELLINGTON STREET WITH DIVERSION SHEET 3					
Designed	DP	03.10.25	Eng Chk.	x	x
Drawn	DP	03.10.25	Coordination	x	x
Dwg Chk.	DS	03.10.25	Approved	x	x
Scale at A3	1:500	Project	x	Status	B
Drawing No	AUX-TM-AMEY-495-BOROUGH_RD-CYCLE-SCHEME-PH2A_B	Rev	X		
A3					